

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 February 2006 (23.02.2006)

PCT

(10) International Publication Number
WO 2006/018261 A1

(51) International Patent Classification⁷: **A61M 15/00**,
B65D 83/04

(21) International Application Number:
PCT/EP2005/008842

(22) International Filing Date: 12 August 2005 (12.08.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0418278.8 16 August 2004 (16.08.2004) GB

(71) Applicant (for all designated States except US): **GLAXO GROUP LIMITED** [GB/GB]; Glaxo Wellcome House, Berkeley Avenue, Greenford Middlesex UB6 0NN (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JONES, Christopher, John** [GB/GB]; DCA Design International Limited, 19 Church Street, Warwick Warwickshire CV34 4AB (GB). **LINTELL, Daniel, Thomas, De Sausmarez** [GB/GB]; c/o GlaxoSmithKline, Park Road, Ware Hertfordshire SG12 0DP (GB). **MAY, James, John** [GB/GB];


DCA Design International Limited, 19 Church Street, Warwick Warwickshire CV34 4AB (GB). **PALMER, Mark, Gregory** [GB/GB]; GlaxoSmithKline, Park Road, Ware Hertfordshire SG12 0DP (GB). **TANSLEY, Robert, William** [GB/GB]; Warwick Design Consultants Limited, 12 Waterloo Park Estate, Bidford on Avon Warwickshire B50 4JH (GB).

(74) Agents: **RICE, Jason, Neale** et al.; GlaxoSmithKline, Corporate Intellectual Property (CN925.1), 980 Great West Road, Brentford Middlesex TW8 9GS (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: MEDICAMENT DISPENSER



(57) Abstract: There is provided a sheet driver (218a) for use in a medicament dispenser including a medicament carrier (100) having a plurality of pockets (104) for containing medicament wherein said pockets (104) are spaced along the length of and defined between first and second sheets (110, 112) secured to each other and separable by drivable pulling action, the sheet driver (218a) comprising a base (220); ascending from the base (200), a shaft (230) defining a rotational axis; on the base (220), a drive surface (225) for receipt of drive to rotate the base (220) about the rotational axis; about the shaft (230), a torsion spring (240) defining first and second spring legs (242, 244); mounting about the shaft (230) and the torsion spring (240) for rotation about the rotational axis, a hub (250) defining a hub surface for receipt of a sheet (110, 112) of the medicament carrier (100). A first leg receiver (224) of the base (220) receives the first spring leg (242) of the torsion spring (240) and a second leg receiver (252) of the hub (250) receives the second spring leg (244) of the torsion spring (240) such that relative rotation of the base (220) and the hub (250) results in tensioning of the torsion spring (240).

WO 2006/018261 A1



(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Medicament dispenser

Technical field

5

The present invention relates to a sheet driver component for use in a medicament dispenser for dispensing medicament, in which medicament in powder or tablet form is carried by an elongate blister strip comprising a base sheet having pockets defined therein and a lid sheet provided thereto.

10

Background to the invention

The use of inhalation devices in the administration of medicaments, for example in bronchodilation therapy is well known. Such devices generally comprise a body or housing within which a medicament carrier is located. A known inhalation device has 15 a medicament carrier in the form of an elongate blister strip containing a number of discrete doses of medicament in powder or tablet form. The elongate blister strip comprises a base sheet having pockets defined therein and a lid sheet provided thereto, wherein the base sheet and lid sheet are peelably separable to allow access 20 to the contents of each pocket. Such devices typically contain a mechanism of accessing these doses comprising peeling means for peeling the lid sheet away from the base sheet. The medicament is thereby made available for delivery to the patient.

25 Suitable peeling means are positioned to peel apart a base sheet and a lid sheet of a pocket at an opening station of the device. The peeling means typically includes a (lid or base) sheet driver for pulling apart a lid sheet from a base sheet of a pocket that has been received at the opening station. In one aspect, the sheet driving means comprises a fixed-diameter wheel on which the (e.g. lid) sheet is wound, the 30 wheel having an effective winding surface, the diameter of which increases as more (e.g. lid) sheet is wound about said wheel.

A problem encountered with the use of such a fixed-diameter wheel as the sheet driver for driving a sheet of a medicament carrier is that as the sheet winds up around the wheel the effective winding diameter of the wheel increases, and
5 therefore its effective lateral pulling action (i.e. length of pull) also increases. This is problematic because it is desirable that on actuation, a definable pull action is experienced by the medicament carrier pocket at the opening station to ensure that a generally uniform indexing / opening effect is experienced by each pocket of the medicament carrier. In general terms, insufficient pull action will result in failure to
10 open up the pocket whilst excess pull will put stress on the mechanical components and increase the force required to actuate the dispenser.

A solution to the above problem has been proposed in Applicant's PCT Patent Application No. WO 03/035509, in which compensating means are provided to
15 compensate for any increase in the diameter of the effective winding surface of the wheel during use of the dispenser and thereby to ensure that said medicament carrier is uniformly indexed upon each actuation of said dispensing mechanism.

The Applicant has now found that a (lid or base) sheet driver having the form of a
20 hub incorporating compensating means in the form of a central shaft-mounted torsion spring provides particularly effective compensation for this increase in diameter.

Summary of the invention

25

According to one aspect of the present invention there is provided a sheet driver for use in a medicament dispenser including a medicament carrier having a plurality of pockets for containing medicament wherein said pockets are spaced along the length of and defined between first and second sheets secured to each other and
30 separable by drivable pulling action, said sheet driver comprising

- (a) a base;
- (b) extending from said base, a shaft defining a rotational axis;
- 5 (c) at said base, a drive surface for receipt of drive to rotate the base about said rotational axis;
- (d) about said shaft, a torsion spring defining first and second spring legs;
- 10 (e) mounting about the shaft and said torsion spring for rotation about the rotational axis, a hub defining a hub surface for receipt of a sheet of said medicament carrier,

wherein a first leg receiver of the base receives said first spring leg of the torsion
15 spring and a second leg receiver of said hub receives said second spring leg of the torsion spring such that relative rotation of the base and the hub results in tensioning of the torsion spring.

The present invention provides a sheet driver for use in a medicament dispenser
20 including a medicament carrier having a plurality of pockets for containing medicament wherein said pockets are spaced along the length of and defined between first and second sheets secured to each other and separable by drivable pulling action.

25 The sheet driver comprises a base, typically of circular form (e.g. disc-shaped).

Extending (e.g. ascending) from the base, there is provided a shaft. The shaft may be formed integral with the base or it may be provided as a separate part to the base for fixing thereto. The shaft defines a rotational axis about which the hub is rotatable.

Provided at the base, there is a drive surface for receipt of drive to rotate the base about the rotational axis. Suitably, the base has circular form and the drive surface extends circumferentially about the base.

- 5 Preferably, the drive surface is geared (i.e. defines a gearing surface), although other types of drive surfaces are envisaged including those responsive to frictional and belt drives.

In one aspect, the drive surface is integral with the base. Suitably, the base defines a
10 rim and the drive surface is provided to the rim.

In another aspect, the drive surface is provided to a separate part, which associates with the base.

- 15 In a particular aspect, the drive surface is provided to a ring that fits over and is received by (e.g. engaged by) a rim of the base. Suitably, the drive surface is provided to the outer circumferential surface of the ring.

In one embodiment, the inner circumferential surface of the ring is also provided with
20 gearing and the base is provided with a ratchet arm such that the base and ring are in ratcheted engagement. Such ratcheted engagement provides that the ring may only be rotated relative to the base in one rotational sense (e.g. only clockwise or only anti-clockwise) with rotation in the other rotational sense being prevented by the ratchet interaction between inner, geared surface of the ring and the ratchet arm of
25 the base.

About said shaft, there is provided a torsion spring. The term 'spring' herein is used to mean any resilient spring-like means, which may be tensioned. The torsion spring defines first and second spring legs that typically extend away (e.g. protrude) from
30 the ends (e.g. top and bottom) of the spring.

Suitably, the spring is a coiled spring. In one aspect, the spring legs protrude away from the spring in a direction perpendicular to the rotational axis defined by the coils of the spring. In another aspect, the spring legs protrude away from the spring in a direction parallel to the rotational axis defined by the coils of the spring.

5

Mounted about the shaft and the torsion spring for rotation about the rotational axis, there is provided a hub defining a hub surface for receipt of a lid or base sheet, preferably lid sheet of said medicament carrier. The hub generally fits over the torsion spring and shaft. The hub itself has a fixed diameter, although its effective
10 winding diameter (i.e. wheel plus thickness of lid or base sheet wound there around) will vary in use as a sheet is accommodated thereby. The hub is typically of solid construction and essentially incompressible in nature, at least about its diameter.

In aspects, the hub is mounted about the shaft such that it is rotatable in either a
15 clockwise or anti-clockwise sense relative to the base, and hence such that the torsion spring may also be tensed in one or other sense.

Suitably, the hub is provided with means for engaging the end of a sheet.

20 In one aspect, the engaging means comprise surface markings or coatings provided to the hub to enhance the frictional contact between the hub and the sheet.

In another aspect, loop-engaging means (e.g. a peg, hook, notch or slot) are provided to the hub for engaged receipt of a looped end of a sheet.

25

The torsion spring of the sheet driver herein, acts to compensate for any increase in the diameter of the effective winding surface of the fixed-diameter hub during winding of sheet thereabout. It is therefore essential that the sheet driver allow for tensioning of the torsion spring. Accordingly, a first leg receiver of the base receives
30 the first spring leg of the torsion spring and a second leg receiver of the hub receives

the second spring leg of the torsion spring such that relative rotation of the base and the hub results in tensioning of the torsion spring.

In a preferred aspect, the hub and the base are provided with a lock for mutually
5 locking the rotation of the hub relative to the base. Suitably, the lock locates at a defined rotational spacing from a start position at which the torsion spring is not tensioned, and the or each locking position (i.e. when lock is engaged) thereby defines a known tensioning of the torsion spring.

10 In one aspect, variation of the 'locking position' is achievable by variation of the leg angle defined by the spring leg(s) of the torsion spring.

To apply a known tension to the torsion spring, the hub is therefore rotated (either clockwise or anti-clockwise) from the start position to a particular locking position, at
15 which the lock engages.

In one aspect, the hub is provided with a locking pin receivable by one or more locking pin receivers of the base. In another aspect, the base is provided with a locking pin receivable by one or more locking pin receivers of the hub.

20

According to another aspect of the present invention there is provided a medicament dispenser for use with medicament carrier having a plurality of pockets for containing medicament wherein said pockets are spaced along the length of and defined between first and second sheets secured to each other and separable by drivable
25 pulling action, said dispenser having an internal dispensing mechanism for accessing said medicament contained within said medicament carrier, said mechanism comprising,

a) an opening station for receiving a pocket of said medicament carrier;

30

b) peeling means positioned to engage a base sheet and a lid sheet of a pocket which has been received in said opening station for peeling apart such a base sheet and lid sheet, to open such a pocket, said peeling means including a sheet driver as described hereinbefore for pulling apart a lid sheet and a base sheet of a pocket that
5 has been received at said opening station;

c) an outlet, positioned to be in communication with an opened pocket through which a user can remove medicament from such an opened pocket; and

10 d) indexer for indexing in communication with said outlet, pockets of a medicament carrier in use with said medicament dispenser, said indexer being interconnected with said sheet driver such that movement of one correlates with the movement of the other.

15 According to a further aspect of the present invention there is provided a medicament dispenser for use with plural medicament carriers, each having a plurality of pockets for containing medicament wherein said pockets are spaced along the length of and defined between first and second sheets secured to each other and separable by drivable pulling action, said dispenser having an internal
20 dispensing mechanism for accessing said medicament contained within each of said plural medicament carriers, said mechanism comprising,

a) an opening station for receiving a pocket of each of said plural medicament carriers;

25

b) peeling means positioned to engage a base sheet and a lid sheet of a pocket which has been received in said opening station for peeling apart such a base sheet and lid sheet, to open such a pocket, said peeling means including a sheet driver as described hereinbefore for pulling apart a lid sheet and a base sheet of a pocket that
30 has been received at said opening station;

c) an outlet, positioned to be in communication with an opened pocket through which a user can remove medicament from such an opened pocket; and

d) indexer for indexing in communication with said outlet, pockets of each of said
5 plural medicament carriers in use with said medicament dispenser, said indexer being interconnected with said sheet driver such that movement of one correlates with the movement of the other.

The sheet driver comprises a fixed-diameter hub on which said base or lid sheet,
10 preferably lid sheet is wound, said hub having an effective winding surface, the diameter of which increases as more sheet is wound about said hub.

The torsion spring acts to compensate for any increase in the diameter of the effective winding surface of the fixed-diameter hub during use of the dispenser and
15 to thereby ensure that said medicament carrier is uniformly indexed upon each actuation of said dispensing mechanism. The torsion spring also acts to ensure that a minimum peeling force between the base sheet and lid sheet is present during actuation of the dispensing mechanism.

20 In particular, the torsion spring act such as to vary the drive function characteristics of the hub to compensate for any increase in the diameter of the effective winding surface of the hub during use of the dispenser. Thereby, the medicament carrier is uniformly indexed (i.e. typically indexed by the same length of strip) as a result of each actuation of the dispensing mechanism, and the pocket opening action
25 experienced by the strip is also uniform.

The medicament dispenser herein is suitable for use with a medicament carrier having a plurality of pockets for containing medicament wherein said pockets are essentially uniformly spaced along the length of and defined between two peelably
30 separable sheets secured to each other. The medicament carrier is generally in the form of an elongate, peelable blister strip.

It will have been appreciated that the torsion spring functions such as to compensate for an increase in the diameter of the effective winding surface of the wheel during use of the dispenser. It will be appreciated that the initial effective winding surface
5 and associated initial drive 'speed' of the hub is principally a function of the (fixed) initial diameter of the hub. Variations are envisaged herein where that initial effective winding surface is selected to define particularly selected initial drive characteristics of the hub.

10 In one variation sometimes called 'one way take up' mode, the initial effective winding surface is selected such as to initially provide ideal (i.e. uniform) indexing of the medicament carrier. As lid sheet winds up around the hub the effective winding surface increases and the torsion spring acts such as to compensate for that increase.

15

In another variation sometimes called 'two way take up' mode, the initial effective winding surface is selected such as to initially provide non-ideal (i.e. non-uniform) indexing of the medicament carrier because the diameter of the hub is insufficiently great. As lid sheet winds up around the hub the effective winding surface increases
20 to an ideal diameter and then on further winding up continues to increase to a non-ideal (i.e. too great diameter). In this embodiment it will be appreciated that the degree and nature of compensation provided by the torsion spring will vary over the winding up function. The torsion spring initially acts such as to compensate for the insufficient wheel diameter. That compensation then decreases to zero at the point
25 where the diameter of the effective winding surface is ideal. The compensation then progressively acts such as to compensate for a too great effective winding surface. This approach has the advantage of overall reducing the (average) compensating torsion force experienced by the medicament carrier from a defined zero (i.e. the ideal) and enables the use of less powerful tensioning means (e.g. a smaller torsion
30 spring). In a preferred aspect of this variation, the ideal effective winding surface diameter is selected to correspond approximately to the point at which half of the lid

sheet is wound up on the hub, in which case the average (i.e. mean) compensating action experienced is by the carrier over a full usage cycle is close to zero.

Suitably, said indexer comprises a rotatable index wheel having recesses therein,
5 said index wheel being engageable with a medicament carrier in use with said medicament dispenser such that said recesses each receive a respective pocket of the base sheet of a medicament carrier in use with said medicament dispenser.

Alternatively, said index means may comprise an indexing ratchet which is moveable
10 between a locked position whereby said ratchet engages a pocket on said medicament carrier and prevents further peeling thereof, and a release position allowing free movement of said medicament carrier, and actuation of said medicament dispenser actuates said sheet driver and releases said index ratchet from said medicament carrier to allow peeling thereof.

15 Suitably, the medicament dispenser further comprises an indexing lever for actuating said dispenser wherein said indexing lever is interconnected with said indexer and/or said sheet driver.

20 In one aspect, the sheet driver and/or the indexer are operated by an electronic drive system. The electronic drive system may also be used in conjunction with a mechanical drive system.

The electronic drive typically comprises a motor, preferably an electrically powered
25 motor. The motor may provide linear or rotary drive, but in general, rotary motors are most suitable. The motor may for example, comprise a DC electric motor, a piezoelectric (PZ) motor, an ultrasonic motor, a solenoid motor or a linear motor. Preferably, the electronic drive system comprises a DC motor, a PZ motor or an ultrasonic motor.

Suitably, the peeling means additionally comprises a guide for guiding the lid sheet and base sheet along separate paths at the opening station. The lid sheet is passed around the guide portion onto the sheet driver.

- 5 Suitably, the guide comprises a roller mechanism. The lid sheet is fed over the rollers onto the sheet driver.

Suitably, the internal mechanism additionally comprises a first chamber in which the strip is initially housed and from which it is dispensed and a second chamber to
10 receive the used portion of the base sheet after it has been indexed and separated from the lid sheet.

Suitably, a wall separates the first chamber and second chamber. In one aspect, the wall is movable to adjust the size of said first and second chambers. In another
15 aspect, the wall is flexibly movable to adjust the size of the first and second chambers. In a further aspect, the second chamber is expandable to create space for the growing coil of the used portion of the base sheet.

Suitably, the internal mechanism further comprises a third chamber to receive the
20 used portion of the lid sheet and a fourth chamber that houses the indexer. The fourth chamber may communicate via a slit, which in turn extends upwardly within a mouthpiece or exit channel and communicates with air inlets.

Suitably, the internal mechanism additionally comprises a crushing wheel to crush
25 the medicament pockets after the medicament has been removed from them. The crushing wheel therefore reduces the space, which the used portion of the base sheet takes up.

Typically, the internal mechanism for accessing said medicament contained within
30 said medicament carrier is housed within a cassette.

In one aspect, the invention provides a medicament dispenser for dispensing medicament comprising: a body; a holder, shaped to fit within said body and movable relative to said body; and receivable by said holder, said cassette containing said medicament carrier.

5

Suitably, movement of the holder relative to the body results in movement of the cassette between a first position and a second position such that the cassette is reversibly removable from the holder when the cassette is in the second position.

- 10 Suitably, the first position comprises a dispensing position. Preferably the second position comprises a non-dispensing position. The cassette is therefore only removable from the holder when the cassette is in the non-dispensing position.

Suitably, the holder and body include attaching means to attach the holder to the
15 body. Preferably said attaching means comprise a snap fit mechanism.

Suitably, said snap fit mechanism comprises a pin and hole system.

Suitably, the holder is pivotally movable relative to the body. Alternatively, the holder
20 is rotationally movable relative to the body.

Suitably, the holder additionally comprises a stop to limit movement of the holder relative to the body. The stop abuts against the edge of the body at two points when it is rotated. At these points the holder may be designed to click into place.
25 Therefore when the stop abuts one body edge then it is clicked into the dispensing position and when the stop abuts the other body edge then it is clicked into the non-dispensing position.

Suitably, the holder is slidably movable relative to the body.

30

Suitably, the holder additionally comprises a catch to retain the cassette. The catch may for example comprise a sprung pin that fits into a hole or an integral catch that deforms when pressed allowing removal of the cassette.

- 5 Suitably, the catch is child resistant. Child resistance may be realised by having a system that forces the user to perform two actions at once to remove the cassette. Other features of the catch may include shock or impact resistance, the ability to lock the catch and orientation features to ensure that the cassette can only be inserted one way. The catch should also be easy to manufacture and assemble, be robust,
- 10 be composed of a minimal number of components and intrude minimally into the space into which the cassette is inserted.

Suitably, the holder includes guide means to guide the cassette into the holder. Preferably said guide means comprise guide rails. Alternatively the guide means

15 comprise grooves, indentations or other shaping or surface details to define a 'lock and key' relationship between the holder and the cassette. Colour guides, arrows and any other surface markings may also be employed.

Suitably, the cassette additionally comprises an indexing lever. The indexing lever

20 has a finger tab located outside the body of the cassette. The rest of the indexing lever is located within the cassette. The indexing lever may have teeth at its tail end and/or teeth along its mid portion.

Suitably, the cassette additionally comprises a mouthpiece.

25

In one aspect, said mouthpiece is extendible. The mouthpiece extends as the cassette and holder are moved from the non-dispensing position to the dispensing position.

30 Alternatively, the mouthpiece is retractable. The mouthpiece retracts as the cassette and holder are moved from the dispensing position to the non-dispensing position.

The medicament dispenser may also be designed for nasal inhalation of a powdered medicament and may therefore incorporate a nosepiece as an alternative to a mouthpiece. If the medicament is in solid form, the dispenser may incorporate an
5 exit channel for tablet release.

Suitably, the body covers the mouthpiece and indexing lever when the cassette is in the non-dispensing position. This avoids the need for a separate cover and protects the mouthpiece from the ingress of dirt and contaminants during storage.

10

Suitably, the cassette additionally comprises a raised portion to fit against the holder. The raised portion is located at the opposite end of the cassette to the mouthpiece/nosepiece/exit and indexing lever and prevents the incorrect insertion of the cassette into the holder since it is too wide to fit into the holder. The raised
15 portion is shaped such that it fits against a cut away part of the holder. Preferably said raised portion includes a section that is raised to define a grip portion.

Suitably, at least a portion of the holder and body are shaped for ease of grip by the user. Suitably, operation of the device may be performed with one hand.

20

Suitably, the body additionally comprises at least one brush or wiper blade located along its top or bottom side that brush against the top and bottom surfaces of the inside of the cassette. The brush or wiper blade acts to close off the chamber for enclosing the medicament carrier from the rest of the body of the cassette and to
25 prevent any loose powder from entering the rest of the cassette. Loose powder may enter the chamber from the used portion of the blister strip if the patient indexes the strip by pressing the lever when they do not intend to take a dose or when they fail to inhale all the powder.

30 Suitably, the medicament dispenser comprises an actuation or dose counter for counting the number of actuations of the indexing lever or releases of dose from the

cassette. The dose counter may count the number of doses left to be taken or the number of doses taken. Suitably, said dose counter is electronic. Alternatively, said dose counter is mechanical.

5 Alternatively, the blister strip has printed numbers on it corresponding to the doses in the pockets. Preferably said printed numbers are visible through a window in the cassette. The device may be assembled as follows. The holder is snap fitted into the body. The cassette is assembled separately. The body of the cassette is formed, preferably in two sections with any necessary spindles or integral
10 components formed into the base. Individual components such as indexing wheels, lid winding mechanisms, guide portions etc are then assembled into the base. Finally the medicament containing blister strip (or other suitable medicament carrier) may be inserted into the cassette. This may be wound into the device before the lid is attached to the cassette and the cassette sealed. Alternatively, the cassette may
15 be formed completely apart from a hole left in its side for insertion of the blister strip or medicament carrier. The hole may then be sealed to complete the cassette. This second method of inserting the medicament carrier into the device has the advantage that it is much simpler.

20 Suitably, the medicament dispenser additionally comprises an electronic data management system. The electronic data management system has input/output capability and comprises a memory for storage of data; a microprocessor for performing operations on said data; and a transmitter for transmitting a signal relating to the data or the outcome of an operation on the data.

25

Suitably, the medicament dispenser additionally comprises a data input system for user input of data to the electronic data management system. Preferably, the data input system comprises a man machine interface (MMI) preferably selected from a keypad, voice recognition interface, graphical user interface (GUI) or biometrics
30 interface.

Suitably, the system additionally comprises a visual display unit for display of data from the electronic data management system to the user. The display may for example, comprise a screen such as an LED or LCD screen. More preferably the visual display unit is associable with the body of the medicament dispenser.

5

Suitably, the medicament dispenser additionally comprises a datalink for linking to a local data store to enable communication of data between the local data store and the electronic data management system. The datastore may also comprise data management, data analysis and data communication capability.

10

The medicament dispenser may additionally comprise a safety mechanism to prevent unintended multiple actuations of the dispensing mechanism. The patient is thereby protected from inadvertently receiving multiple doses of medicament in a situation where they take a number of short rapid breaths. More preferably, the safety mechanism imposes a time delay between successive actuations of the release means. The time delay is typically of the order of from three to thirty seconds.

Suitably, the medicament dispenser additionally comprises a release detector for detecting release of medicament from the cassette, wherein said release detector transmits release data to the electronic data management system.

Suitably, the medicament dispenser additionally comprises a shake detector for detecting shaking of the medicament container (e.g. prior to actuation of the dispensing mechanism), wherein said shake detector transmits shake data to the electronic data management system.

Suitably, any actuation detector, release detector, or shake detector comprises a sensor for detecting any suitable parameter such as movement. Any suitable sensors are envisaged including the use of optical sensors. The release detector may sense any parameter affected by release of the medicament such as pressure,

30

temperature, sound, moisture, carbon dioxide concentration and oxygen concentration.

The medicament dispenser herein suitably contains a medicament carrier having a plurality of pockets for containing medicament wherein said pockets are essentially uniformly spaced along the length of and defined between two peelably separable sheets secured to each other. The medicament carrier is generally in the form of an elongate, peelable blister strip.

- 10 Suitably, the peelable blister strip comprises a base sheet in which blisters are formed to define pockets therein for containing distinct medicament dose portions and a lid sheet which is hermetically sealed to the base sheet except in the region of the blisters in such a manner that the lid sheet and the base sheet can be peeled apart. The base and lid sheets are typically sealed to one another over their whole width except for the forward end portions where they are typically not sealed to one another at all. Thus, separate base and lid sheet forward end portions are presented at the end of the strip. The respective base and lid sheets are peelably separable from each other to (e.g. separately) release the contents of each pocket.
- 20 In one aspect, the leading end of either the base or lid sheet or is looped to enable better receipt by the hub of the sheet driver herein.

In one aspect, the medicament carrier comprises a peelable blister strip in laminate form. Suitably, the laminate comprises material selected from the group consisting of metal foil, organic polymeric material and paper. Suitable metal foils include aluminium or tin foil having a thickness of from 5 to 100 μ m, preferably from 10 to 50 μ m, such as 20 to 30 μ m. Suitable organic polymeric materials include polyethylene, polypropylene, polyvinyl chloride and polyethylene terephthalate.

- 30 Suitably, the lid sheet comprises at least the following successive layers: (a) paper; adhesively bonded to (b) polyester; adhesively bonded to (c) aluminium foil; that is

coated with a heat seal lacquer for bonding to the base sheet. The thickness of each layer may be selected according to the desired properties but is typically of the order of from 5 to 200 micron, particularly from 10 to 50 micron.

- 5 Suitably, the base sheet comprises at least the following successive layers: (a) oriented polyamide (OPA); adhesively bonded to (b) aluminium foil; adhesively bonded to (c) a third layer comprising a polymeric material (e.g. polyvinyl chloride).

Various known techniques can be employed to join the lid and base sheet and hence
10 to seal the blisters of the peelable blister strip. Such methods include adhesive bonding, hot metal bonding, hot metal welding, radio frequency welding, laser welding, ultrasonic welding and hot bar sealing. The lid sheet and base sheet of the peelable blister strip are particularly sealable by 'cold form' sealing methods, which are conducted at lower temperatures than conventional heat sealing methods. Such
15 'cold form' sealing methods are of particular utility where the medicament or medicament formulation for containment within the blister is heat sensitive (e.g. degrades or denatures on heating). Suitable 'cold form' sealing methods are conducted at a temperature in the range of 150-250°C, more preferably, 210-240°C.

- 20 The medicament may comprise a capsule, pellet or tablet. Alternatively, the medicament may be in powdered form. Preferably, when in powdered form the medicament comprises a drug. Preferably the drug is selected from the group consisting of albuterol, salmeterol, fluticasone propionate and beclomethasone dipropionate and salts or solvates thereof and any combination thereof. Preferably
25 said combination comprises salmeterol xinafoate and fluticasone propionate.

Suitably, the powdered medicament additionally comprises an excipient. Suitably, said excipient is a sugar.

- 30 In another aspect, the invention provides the use of a medicament dispenser as described hereinbefore.

Brief Description of the Drawings

The invention will now be described with reference to the accompanying drawings in
5 which:

Figure 1 shows a perspective view of a medicament carrier for with a medicament dispenser in accord with the present invention;

10 Figures 2a to 2k show perspective views of details of the assembly of a sheet driver herein;

Figures 3a to 3f show perspective views of the incorporation of the sheet driver assembled as in Figures 2a to 2k into a medicament dispenser herein

15

Figure 4a shows a perspective view of a medicament dispenser having a first elongate strip form medicament carrier received thereby, and the insertion of second elongate strip form medicament carrier there into;

20 Figure 4b shows the medicament dispenser of Figure 4b with the second elongate strip form medicament carrier received thereby;

Figures 5a to 5h show perspective views of details of the assembly of a second sheet driver herein; and

25

Figures 6a to 6d shows perspective views of the attachment of the end of a medicament carrier to the second sheet driver of Figures 5a to 5h.

30

Detailed Description of the Drawings

Referring now to the Figures, Figure 1 shows a medicament carrier 100 for use in accord with the medicament dispenser of the present invention. The medicament carrier comprises a flexible strip 102 defining a plurality of pockets 104, 106, 108 each of which contains a dose of medicament that can be inhaled, in the form of powder.

The strip comprises a base sheet 110 in which blisters are formed to define the pockets 104, 106, 108 and a lid sheet 112 which is hermetically sealed to the base sheet except in the region of the blisters in such a manner that the lid sheet 112 and the base sheet 110 can be peeled apart. The sheets 110, 112 are sealed to one another over their whole width except for the leading end portions 114, 116 where they are preferably not sealed to one another at all. The leading end portion 116 of the lid sheet 112 is looped for engagement with a hub of a sheet driver, as will be described in more detail hereinafter. The lid 112 and base 112 sheets are each preferably formed of a plastics/aluminium laminate and are preferably adhered to one another by heat sealing.

The strip 102 is shown as having uniformly-spaced elongate pockets 104, 106, and 108 that run transversely with respect to the length of the strip 102. This is convenient in that it enables a large number of pockets 104, 106, 108 to be provided in a given strip 102 length. The strip 102 may, for example, be provided with sixty or one hundred pockets but it will be understood that the strip 102 may have any suitable number of pockets.

Figures 2a to 2k show details of the assembly of a first sheet driver herein. In respect of each of the Figures, only the most relevant parts for that Figure are labelled.

Referring initially to Figures 2a and 2b, circular form base 220 may be seen to have geared drive surface 225 provided to circumferential rim 222 and integral, upwardly

extending shaft 230. Torsion spring 240 having lower 242 and upper 244 spring ends is lowered onto shaft 230 such that lower spring end 242 engages in spring leg retainer slot 224 of base 220. The shaft 230 also has a protruding lip 234, the function of which will become clearer from the later description.

5

Referring now to Figures 2c to 2e, hub 250 is lowered onto shaft 230 such that it sits over torsion spring 240. It may be seen that upper spring leg 244 of torsion spring 240 is received by spring leg retainer slot 252 provided to the inner part of the hub 250. Upper end 232 of the shaft 230 protrudes through central aperture 254 of the lid
10 end 256 of the hub 250. The hub 250 may also be seen to be provided with an upwardly standing hook 258 part arranged for receipt of the looped end of a sheet, as will be described in more detail hereinafter.

Referring now to Figures 2f to 2h, hub 250 is now rotated in a clockwise direction (in
15 alternative embodiments, anti-clockwise rotation is envisaged) by a defined rotation (in this case about 135°) relative to the base 220. It will be appreciated that because the spring legs of torsion spring (not visible in Figures 2f to 2h) attach respectively to the base 220 and hub 250, such rotation results in tensing of the torsion spring. The extent of defined rotation is selected such as to align a stepped wall 255 of the
20 underside of the hub 250 with the edge of the wall 223 that forms part of retainer slot 224 for lower spring leg 242.

As shown at Figures 2i to 2k, the hub 250 is then pressed home (i.e. downwards towards the base 220) such that the central aperture 254 thereof snap-fits over the
25 lip 234 of shaft 230 to retain the hub 250 to the base 220. The torsion spring (not visible in Figures 2i to 2k) does not unwind from its tensed state as a result of the interaction of the stepped wall 255 of the underside of the hub 250 with the edge of the wall 223 that forms part of retainer slot 224 for lower spring leg 242 (all visible in Figure 2i only).

30

The sheet driver assembly is now ready for use in a suitable medicament dispenser.

Figures 3a to 3f show perspective views of the assembly of the drive unit 260 of a medicament dispenser herein. The drive unit 260 is arranged for use in a medicament dispenser for use with plural medicament carriers, each of the type shown at Figure 1 and having a plurality of pockets 104, 106, 108 for containing
5 medicament wherein said pockets 104, 106, 108 are spaced along the length of and defined between a base sheet 110 and lid sheet 112, the sheets 110, 112 secured to each other and peelably separable by drivable pulling action

Referring to Figure 3a, drive unit 260 is arranged for receipt of first and second sheet
10 drivers 218a, 218b such that the hubs 250a, 250b thereof extend through apertures 262a, 262b provided to the base 261 of the drive unit. The bases 220a, 220b of the drivers 218a, 218b protrude upwards from the apertures 262a, 262b such that the respective hubs 250a, 250b are rotatably drivable by rotary drive motion of the geared drive surfaces 225a, 225b of the respective bases 220a, 220b.

15 Referring to Figure 3b, the geared drive surfaces 225a, 225b of the respective bases 220a, 220b of may be seen to interact with complex gear train 265 provided to the base 261 of the drive unit 260. The gear train 265, and hence rotation of each respective base 220a, 220b is ultimately drivable by primary index gear 270, which
20 interacts with ratchet unit 272, the purpose of which is to prevent reverse rotation of the primary index gear 270.

Referring to Figure 3c, the primary index gear 270 may be seen in turn, to be drivable by index lever 274, which pivots about pivot point 275. Thus, actuation of
25 the sheet drivers 218a, 218b is by pivotal movement of the index 274 to rotate the primary index gear 270, which accordingly results in transfer of drive through gear train 265 to the geared drive surfaces 225a, 225b of the bases 220a, 220b of both of the sheet drivers 218a, 218b.

30 Referring now to Figures 3d to 3f, first 282 and second 284 shell parts of dispenser housing 280 are applied to the drive unit 260. It may be seen that mouthpiece 281 is

defined by shell parts 282, 284 in tandem. In Figures 3e and 3f (only) movable cover 286 is also seen to have been fitted over peg 273 of index lever 274 such that movement of the cover 286 will result in movement of the index lever 274, and thus in turn actuate the mechanism for driving the sheet drivers 218a, 218b. Overall, in use, patient movement of the movable cover 286 provides the means for advancing the sheet drivers 218a, 218b, and hence the individual medicament doses held within pockets of the medicament carrier.

The interaction of the medicament carriers with the drive unit of the dispenser of Figures 3e and 3f may be better understood by reference to Figures 4a and 4b.

Figure 4a shows the medicament dispenser of Figure 3e (a) having the top shell 282 and movable cover 286 removed (for better visibility of the inner workings); and (b) having a first elongate strip form medicament carrier 302a received thereby, and illustrating the insertion of second elongate strip form medicament carrier 302b there into. Figure 4b shows the medicament dispenser of Figure 4b with the second elongate strip form medicament carrier 302b received thereby.

In more detail, Figures 4a and 4b illustrate a base unit 360 of a medicament dispenser herein. First and second medicament-containing blister strips 302a, 302b are arranged to be accommodated within respective left and right chambers 390a, 390b of the base unit 360. It will be appreciated that each blister strip 302a, 302b has the form shown in Figure 1. Within the dispenser, each blister strip 302a, 302b engages in respective multi-pocket index wheel 392a, 392b, and successive pockets are thereby guided towards a central opening station 393. The rotation of the index wheels 392a, 392b is optionally coupled together (e.g. via a suitable gear train such as shown in Fig 3b). At the opening station 393, the lid foil 312a, 312b and base foil 314a, 314b parts of each strip 302a, 302b are peelably separable about beak (not clearly visible). The resulting empty base foil 314a, 314b coils up in respective base take-up chambers 315a, 315b. A base foil anchor 317a, 317b anchors the end of each respective base foil 314a, 314b in its chamber 315a, 315b.

The looped end 316a, 316b of each lid foil 312a, 312b of each carrier 302a, 302b is received by upwardly standing hook 358a, 358b part of its respective torsion hub 350a, 350b drive. The inner structure of each torsion hub drive 350a, 350b is as described by reference to Figures 2a to 2k, or in an alternative embodiment is that
5 described by reference to Figures 5a to 5h.

The function of each torsion hub drive 350a, 350b is to ensure a roughly constant driving tension is provided to each strip 302a, 302b over the course of each entire strip length. In particular, each torsion hub 350a, 350b acts to compensate for the
10 variation in drive tension associated with the increase in the effective winding diameter of each hub 350a, 350b as used lid foils 312a, 312b gradually becomes wrapped there around. Thus, uniform indexing of each strip 302a, 302b may be maintained over the entire strip length.

15 In use, the dispenser is primed (typically by means of an actuating lever, for example in the form of a movable cover 286 as shown in Figures 3e, 3f) to drivably actuate each torsion hub drive 350a, 350b associated with each carrier 302a, 302b, thereby causing the leading pocket thereof to be peeled open. Each torsion hub 350a, 350b acts to provide any necessary drive compensation, as described above. To access
20 the contents of the opened pockets the patient then breathes in through the outlet 381 (which is typically shaped as a mouthpiece or nasal nozzle). This results in negative pressure being transmitted through manifold 383 to the opened leading pocket of each strip 302a, 302b at the opening station 393. This in turn, results in the medicament powder contained within each of the opened pockets being drawn out
25 through the common manifold 383 to the outlet 381 and hence to the patient as an inhaled combination medicament dose. It be appreciated that, mixing of each separately delivered component of the combined medicament product happens as the powder is transported from each opened pocket to the outlet 381.

30 Figures 5a to 5h show perspective views of details of the assembly of a second sheet driver herein.

Referring initially to Figures 5a and 5b, circular form base 320 is provided with ratchet arm 321. Ring 323 having a first geared drive surface 325 provided to its outer circumference and a second geared surface 327 provided to its inner circumference is pressed onto the base 320. When pressed home, it may be seen
5 that ratchet arm 321 of the base 320 is in ratcheted engagement with the second (i.e. inner) geared surface 327 of the ring such that the ring 323 may only be rotated in one direction relative to the base 320. Shaft 330 extends away from the base 320.

Referring now to Figures 5c and 5d, torsion spring 340 having lower 342 and upper
10 344 spring ends is lowered onto shaft 330 such that lower spring end 342 engages in spring leg retainer slot 324 of base 320. The shaft 330 also has a protruding notch 334, the function of which will become clearer from the later description.

Referring now to Figures 5e and 5f, hub 350 is lowered onto shaft 330 such that it
15 sits over torsion spring 340. Upper spring leg of torsion spring 340 is received by spring leg retainer slot (not visible) provided to the inner part of the hub 350. Upper end 332 of the shaft 330 protrudes through central aperture 354 of the lid end 356 of the hub 350. The hub 350 may also be seen to be provided with a hook 358 part arranged for receipt of the looped end of a sheet, as will be described in more detail
20 hereinafter.

Referring now to Figures 5g to 5h, hub 350 is now rotated in an anti-clockwise direction (in alternative embodiments, clockwise rotation is envisaged) by a defined rotation (in this case about 90°) relative to the base 320. It will be appreciated that
25 because the spring legs of torsion spring (not visible in Figures 5g to 5h) attach respectively to the base 320 and hub 350, such rotation results in tensing of the torsion spring. The extent of defined rotation is selected such as to align a stepped wall (not visible) of the underside of the hub 350 with the edge of the wall (not visible) that forms part of retainer slot for lower spring leg 342.

The torsion spring (not visible in Figures 5g to and 5h) does not unwind from its tensed state as a result of the ratcheted interaction between the ratchet arm 321 of the base 320 and the inner geared surface 327 of the ring 323.

- 5 One advantage of the 'ratcheted hub' form of sheet driver as shown in Figures 5a to 5h is that it allows for flattening out of any variation of spring tolerances. Such variation of spring tolerance often occurs when springs are manufactured in bulk.

The second sheet driver assembly is now ready for use in a suitable medicament
10 dispenser.

Figures 6a to 6d show the attachment of the end of a medicament carrier to the hub 350 of the second sheet driver of Figures 5a to 5h.

- 15 Figure 6a shows the second sheet driver 318 loaded into a drive unit 360 of a suitable medicament dispenser with the hook 358 part of the hub 350 facing outwards. In Figure 6b, a looped end 316 of the lid sheet 312 of a medicament carrier (of the type shown in Figure 1) is looped over the hook 358 of the hub 350. In Figures 6c and 6d, the sheet driver 318 is rotated thereby causing the lid sheet 312
20 to wrap around the hub 350 until all slack is taken up.

The medicament dispenser herein is suitable for dispensing medicament, particularly for the treatment of respiratory disorders such as asthma and chronic obstructive pulmonary disease (COPD), bronchitis and chest infections. Appropriate
25 medicaments may thus be selected from, for example, analgesics, e.g., codeine, dihydromorphine, ergotamine, fentanyl or morphine; anginal preparations, e.g., diltiazem; antiallergics, e.g., cromoglycate (e.g. as the sodium salt), ketotifen or nedocromil (e.g. as the sodium salt); anti-infectives e.g., cephalosporins, penicillins, streptomycin, sulphonamides, tetracyclines and pentamidine; antihistamines, e.g.,
30 methapyrilene; anti-inflammatory, e.g., beclomethasone (e.g. as the dipropionate ester), fluticasone (e.g. as the propionate ester), flunisolide, budesonide, rofleponide,

mometasone e.g. as the furoate ester), ciclesonide, triamcinolone (e.g. as the
 acetone) or 6α , 9α -difluoro- 11β -hydroxy- 16α -methyl-3-oxo- 17α -propionyloxy-
 androsta-1,4-diene- 17β -carbothioic acid S-(2-oxo-tetrahydro-furan-3-yl) ester;
 antitussives, e.g., noscapine; bronchodilators, e.g., albuterol (e.g. as free base or
 5 sulphate), salmeterol (e.g. as xinafoate), ephedrine, adrenaline, fenoterol (e.g. as
 hydrobromide), formoterol (e.g. as fumarate), isoprenaline, metaproterenol,
 phenylephrine, phenylpropanolamine, pirbuterol (e.g. as acetate), reproterol (e.g. as
 hydrochloride), rimiterol, terbutaline (e.g. as sulphate), isoetharine, tulobuterol or 4-
 hydroxy-7-[2-[[2-[[3-(2-phenylethoxy)propyl]sulfonyl]ethyl]amino]ethyl-2(3H)-
 10 benzothiazolone; adenosine 2a agonists, e.g. 2R,3R,4S,5R)-2-[6-Amino-2-(1S-
 hydroxymethyl-2-phenyl-ethylamino)-purin-9-yl]-5-(2-ethyl-2H-tetrazol-5-yl)-
 tetrahydro-furan-3,4-diol (e.g. as maleate); α_4 integrin inhibitors e.g. (2S)-3-[4-({[4-
 (aminocarbonyl)-1-piperidinyl]carbonyl}oxy)phenyl]-2-[(2S)-4-methyl-2-[[2-(2-
 methylphenoxy) acetyl]amino]pentanoyl]amino] propanoic acid (e.g. as free acid or
 15 potassium salt), diuretics, e.g., amiloride; anticholinergics, e.g., ipratropium (e.g. as
 bromide), tiotropium, atropine or oxitropium; hormones, e.g., cortisone,
 hydrocortisone or prednisolone; xanthines, e.g., aminophylline, choline
 theophyllinate, lysine theophyllinate or theophylline; therapeutic proteins and
 peptides, e.g., insulin or glucagon; vaccines, diagnostics, and gene therapies. It will
 20 be clear to a person skilled in the art that, where appropriate, the medicaments may
 be used in the form of salts, (e.g., as alkali metal or amine salts or as acid addition
 salts) or as esters (e.g., lower alkyl esters) or as solvates (e.g., hydrates) to optimise
 the activity and/or stability of the medicament.

25 Preferred medicaments are selected from albuterol, salmeterol, fluticasone
 propionate and beclomethasone dipropionate and salts or solvates thereof, e.g., the
 sulphate of albuterol and the xinafoate of salmeterol.

Medicaments can also be delivered in combinations. Preferred formulations
 30 containing combinations of active ingredients contain salbutamol (e.g., as the free
 base or the sulphate salt) or salmeterol (e.g., as the xinafoate salt) or formoterol (eg

as the fumarate salt) in combination with an anti-inflammatory steroid such as a beclomethasone ester (e.g., the dipropionate) or a fluticasone ester (e.g., the propionate) or budesonide. A particularly preferred combination is a combination of fluticasone propionate and salmeterol, or a salt thereof (particularly the xinafoate salt). A further combination of particular interest is budesonide and formoterol (e.g. as the fumarate salt).

Generally, powdered medicament particles suitable for delivery to the bronchial or alveolar region of the lung have an aerodynamic diameter of less than 10 micrometers, preferably less than 6 micrometers. Other sized particles may be used if delivery to other portions of the respiratory tract is desired, such as the nasal cavity, mouth or throat. The medicament may be delivered as pure drug, but more appropriately, it is preferred that medicaments are delivered together with excipients (carriers) which are suitable for inhalation. Suitable excipients include organic excipients such as polysaccharides (i.e. starch, cellulose and the like), lactose, glucose, mannitol, amino acids, and maltodextrins, and inorganic excipients such as calcium carbonate or sodium chloride. Lactose is a preferred excipient.

Particles of the powdered medicament and/or excipient may be produced by conventional techniques, for example by micronisation, milling or sieving. Additionally, medicament and/or excipient powders may be engineered with particular densities, size ranges, or characteristics. Particles may comprise active agents, surfactants, wall forming materials, or other components considered desirable by those of ordinary skill.

25

The excipient may be included with the medicament via well-known methods, such as by admixing, co-precipitating and the like. Blends of excipients and drugs are typically formulated to allow the precise metering and dispersion of the blend into doses. A standard blend, for example, contains 13000 micrograms lactose mixed with 50 micrograms drug, yielding an excipient to drug ratio of 260:1. Dosage blends

30

with excipient to drug ratios of from 1000:1 to 1:1 may be used. At very low ratios of excipient to drug, however, the drug dose reproducibility may become more variable.

The present application claims priority from UK patent application No. 04 182 78.8
5 filed on 16 August 2004, the entire content of which is hereby incorporated herein by reference.

It will be understood that the present disclosure is for the purpose of illustration only and the invention extends to modifications, variations and improvements thereto.

10 The application of which this description and claims form part may be used as a basis for priority in respect of any subsequent application. The claims of such subsequent application may be directed to any feature or combination of features described therein. They may take the form of product, method or use claims and may include, by way of example and without limitation, one or more of the following
15 claims:

Claims

1. A sheet driver for use in a medicament dispenser including a medicament carrier having a plurality of pockets for containing medicament wherein said pockets
5 are spaced along the length of and defined between first and second sheets secured to each other and separable by drivable pulling action, said sheet driver comprising

(a) a base;

10 (b) extending from said base, a shaft defining a rotational axis;

(c) at said base, a drive surface for receipt of drive to rotate the base about said rotational axis;

15 (d) about said shaft, a torsion spring defining first and second spring legs;

(e) mounting about the shaft and said torsion spring for rotation about the rotational axis, a hub defining a hub surface for receipt of a sheet of said medicament carrier,

20

wherein a first leg receiver of the base receives said first spring leg of the torsion spring and a second leg receiver of said hub receives said second spring leg of the torsion spring such that relative rotation of the base and the hub results in tensioning of the torsion spring.

25

2. A sheet driver according to claim 1, wherein the base is of essentially circular form.

3. A sheet driver according to either of claims 1 or 2, wherein the shaft is integral
30 with the base.

4. A sheet driver according to any of claims 1 to 3, wherein the drive surface defines a gearing surface.
5. A sheet driver according to any of claims 1 to 4, wherein the drive surface
5 extends circumferentially about the base.
6. A sheet driver according to any of claims 1 to 5, wherein the drive surface is integral with the base.
- 10 7. A sheet driver according to claim 6, wherein the base defines a rim and the drive surface is provided to said rim.
8. A sheet driver according to any of claims 1 to 5, wherein the drive surface is provided to a separate part, which associates with the base.
- 15 9. A sheet driver according to claim 8, wherein said part comprises a ring that fits over and is received by a rim of the base.
10. A sheet driver according to claim 9, wherein the drive surface is provided to
20 the outer circumference of the ring.
11. A sheet driver according to either of claims 9 or 10, wherein an inner circumferential surface of the ring is also provided with gearing and the base is provided with a ratchet arm such that the base and ring are in ratcheted
25 engagement.
12. A sheet driver according to any of claims 1 to 11, wherein the first and second spring legs protrude from first and second ends of the spring.
- 30 13. A sheet driver according to any of claims 1 to 12, wherein the hub fits over the torsion spring and shaft.

14. A sheet driver according to any of claims 1 to 13, wherein the hub is provided with sheet engaging means for engaging the end of a sheet.

15. A sheet driver according to claim 14, wherein the sheet engaging means
5 comprises surface marking or coating provided to the hub to enhance the frictional contact between the hub and the sheet.

16. A sheet driver according to claim 14, wherein the sheet engaging means comprises loop-engaging means for engaged receipt of a looped end of a sheet.

10

17. A sheet driver according to any of claims 1 to 16, additionally comprising a lock for locking the rotation of the hub relative to the base.

18. A sheet driver according to claim 17, wherein the lock locates at a defined
15 rotational spacing from a start position at which the torsion spring is not tensioned, and the or each locking position defines a tensioning of the torsion spring.

19. A sheet driver according to either of claims 17 or 18, wherein the hub is provided with a locking pin receivable by one or more locking pin receivers of the
20 base.

20. A sheet driver according to either of claims 17 or 18, wherein, the base is provided with a locking pin receivable by one or more locking pin receivers of the
hub.

25

21. A medicament dispenser for use with a medicament carrier having a plurality of pockets for containing medicament wherein said pockets are spaced along the length of and defined between first and second sheets secured to each other and separable by drivable pulling action, said dispenser having an internal dispensing
30 mechanism for accessing said medicament contained within said medicament carrier, said mechanism comprising,

- a) an opening station for receiving a pocket of said medicament carrier;
- b) peeling means positioned to engage a base sheet and a lid sheet of a pocket which has been received in said opening station for peeling apart such a base sheet
5 and lid sheet, to open such a pocket, said peeling means including a sheet driver according to any of claims 1 to 20 for pulling apart a lid sheet and a base sheet of a pocket that has been received at said opening station;
- c) an outlet, positioned to be in communication with an opened pocket through
10 which a user can remove medicament from such an opened pocket; and
- d) indexer for indexing in communication with said outlet, pockets of a medicament carrier in use with said medicament dispenser, said indexer being interconnected with said sheet driver such that movement of one correlates with the
15 movement of the other.

22. A medicament dispenser for use with plural medicament carriers, each having a plurality of pockets for containing medicament wherein said pockets are spaced along the length of and defined between first and second sheets secured to each
20 other and separable by drivable pulling action, said dispenser having an internal dispensing mechanism for accessing said medicament contained within each of said plural medicament carriers, said mechanism comprising,

- a) an opening station for receiving a pocket of each of said plural medicament
25 carriers;
- b) peeling means positioned to engage a base sheet and a lid sheet of a pocket which has been received in said opening station for peeling apart such a base sheet and lid sheet, to open such a pocket, said peeling means including a sheet driver as
30 according to any of claims 1 to 20 for pulling apart a lid sheet and a base sheet of a pocket that has been received at said opening station;

c) an outlet, positioned to be in communication with an opened pocket through which a user can remove medicament from such an opened pocket; and

d) an indexer for indexing in communication with said outlet, pockets of each of
5 said plural medicament carriers in use with said medicament dispenser, said indexer being interconnected with said sheet driver such that movement of one correlates with the movement of the other.

23. A medicament dispenser according to either of claims 21 or 22, wherein the
10 indexer comprises a rotatable index wheel having pocket receiving recesses therein.

24. A medicament dispenser according to any of claims 21 to 23, additionally comprising an indexing lever for actuating the indexer and sheet driver.

15 25. A medicament dispenser according to any of claims 21 to 24, wherein the indexing lever couples to a movable cover provided to the dispenser such that movement of the cover results in movement of the indexing lever.

26. A medicament dispenser according to any of claims 1 to 25, wherein the
20 peeling means additionally comprises a guide for guiding the lid sheet and base sheet along separate paths at the opening station.

27. A medicament dispenser according to any of claims 1 to 26, additionally comprising at least one medicament carrier having a plurality of pockets containing
25 medicament wherein said pockets are spaced along the length of and defined between first and second sheets secured to each other and separable by drivable pulling action.

28. A medicament dispenser according to claim 27, wherein said at least one
30 medicament carrier comprises a lid sheet which is hermetically sealed to a base

sheet except in the region of the blisters such that said lid sheet and base sheet can be peeled apart by said drivable pulling action.

29. A medicament dispenser according to either of claims 27 or 28, wherein the
5 leading end of either the base or lid sheet or is looped for receipt by the hub.

30. A medicament dispenser according to any of claims 27 to 29, wherein the medicament is in powdered or tablet form.

10 31. A medicament dispenser according to claim 30, wherein the medicament comprises a drug.

32. A medicament dispenser according to claim 31, wherein the drug is selected from the group consisting of albuterol, salmeterol, fluticasone propionate and
15 beclomethasone dipropionate and salts or solvates thereof and any combination thereof.


33. A medicament dispenser according to claim 32, wherein said combination comprises salmeterol xinafoate and fluticasone propionate.

20

34. A medicament dispenser according to any of claims 30 to 33, wherein the medicament additionally comprises an excipient.

1/21

FIG. 1



2/21

FIG. 2a





FIG. 2b



3/21

FIG. 2c





FIG. 2d



4/21

FIG. 2e





FIG. 2f



5/21

FIG. 2g






FIG. 2h



6/21

FIG. 2i



7/21

FIG. 2j







FIG. 2k






9/21




10/21

FIG. 3c




11/21

FIG. 3d




12/21

FIG. 3e




13/21

FIG. 3f




14/21

FIG. 4a



15/21

FIG. 4b



16/21

FIG. 5a





FIG. 5b



17/21

FIG. 5c







FIG. 5d



18/21



19/21

FIG. 5g





FIG. 5h



20/21

FIG. 6a







FIG. 6b



21/21



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP2005/008842

A. CLASSIFICATION OF SUBJECT MATTER

A61M15/00 B65D83/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61M A61J B65D B41J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2004/067069 A (VALOIS SAS) 12 August 2004 (2004-08-12) page 6, line 16 - page 7, line 9; figures 1-10A page 9, line 1 - page 10, line 17 -----	1,21,22
A	FR 2 659 558 A (GLAXO GROUP LTD) 20 September 1991 (1991-09-20) page 4, line 21 - page 12, line 18; figures 1,2,3a-3c,25-29 -----	1,21,22
A	US 5 582 162 A (PETERSSON ET AL) 10 December 1996 (1996-12-10) column 3, line 16 - column 6, line 48; figures ----- -/-	1,21,22

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 November 2005

Date of mailing of the international search report

25/11/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Zeinstra, H

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP2005/008842

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 03/035509 A (GLAXO GROUP LIMITED; CROSBY, GARY, THOMAS; PALMER, MARK, GREGORY) 1 May 2003 (2003-05-01) cited in the application page 31, line 28 - page 33, line 15; figures 2,3 -----	1,21,22

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2005/008842

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 2004067069	A	12-08-2004	EP 1587565 A2	26-10-2005
FR 2659558	A	20-09-1991	AP 310 A	07-01-1994
			AT 401007 B	28-05-1996
			AT 43791 A	15-10-1995
			AU 675825 B2	20-02-1997
			AU 5926794 A	16-06-1994
			AU 645056 B2	06-01-1994
			AU 7202591 A	05-09-1991
			BE 1003798 A4	16-06-1992
			BR 9100843 A	05-11-1991
			CA 2037421 A1	03-09-1991
			CH 683319 A5	28-02-1994
			CN 1054893 A	02-10-1991
			CN 1107687 A	06-09-1995
			CZ 283168 B6	14-01-1998
			CY 2010 A	20-02-1998
			CZ 9601807 A3	16-12-1998
			DE 4106379 A1	05-09-1991
			DK 37991 A	03-09-1991
			ES 2031763 A6	16-12-1992
			FI 911037 A	03-09-1991
			FI 990115 A	21-01-1999
			FR 2660550 A1	11-10-1991
			GB 2242134 A	25-09-1991
			GR 91100096 A	30-06-1992
			HK 18895 A	17-02-1995
			HK 19195 A	17-02-1995
			IE 910698 A1	11-09-1991
			IL 97396 A	31-12-1995
			IT 1244655 B	08-08-1994
			JP 3110477 B2	20-11-2000
			JP 4220266 A	11-08-1992
			KR 210412 B1	15-07-1999
			LU 87898 A1	16-11-1992
			NL 9100381 A	01-10-1991
			NO 910836 A	03-09-1991
			NO 302929 B1	11-05-1998
			NO 980033 A	05-01-1998
			NZ 237274 A	27-02-1996
			OA 9393 A	15-09-1992
			PL 289264 A1	01-06-1992
			PT 96920 A	29-01-1993
			SE 512934 C2	05-06-2000
			SE 9100582 A	03-09-1991
			RU 2075977 C1	27-03-1997
			ZA 9101516 A	26-02-1992
US 5582162	A	10-12-1996	AT 206941 T	15-11-2001
			AU 674717 B2	09-01-1997
			AU 5582494 A	22-06-1994
			BR 9307537 A	01-06-1999
			CA 2149027 A1	09-06-1994
			DE 69330962 D1	22-11-2001
			DE 69330962 T2	16-05-2002
			EP 0670742 A1	13-09-1995
			FI 952566 A	26-05-1995
			HU 71188 A2	28-11-1995

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2005/008842

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5582162	A	JP 3523255 B2	26-04-2004
		JP 8503403 T	16-04-1996
		NO 952038 A	23-05-1995
		WO 9412230 A1	09-06-1994
WO 03035509	A	01-05-2003	
		BR 0213047 A	05-10-2004
		CA 2463961 A1	01-05-2003
		CN 1571751 A	26-01-2005
		EP 1436217 A1	14-07-2004
		JP 2005506164 T	03-03-2005
		MX PA04003253 A	23-07-2004
		US 2005017017 A1	27-01-2005
		ZA 200402840 A	15-04-2005